

View Online at <https://aerobasegroup.com/nsn/5915-00-057-5804>

Overall Height:

1.906 inches

Body Length:

1.920 inches

Body Width:

1.010 inches

Body Height:

1.500 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

Between 0.959 inches and 0.991 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

Between 0.440 inches and 0.560 inches

Operating Temperature Range:

+0.0/+75.0 degrees celsius

Reference Frequency Per Function:

147.5 kilohertz blank

Source Impedance Rating Per Function:

1.0 kilohms blank

Load Impedance Per Function:

1.0 kilohms blank

Mounting Facility Screw Thread Series Designator:

Unc

Inclosure Type:

Hermetically sealed

Mounting Facility Type And Quantity:

4 threaded stud

Insertion Loss At Reference Frequency Per Function In Decibels:

3.5 blank

Functional Terminal Type And Quantity:

2 tab, solder lug ground 3rd function

Specified Frequencies Of Discrimination Per Function:

143.00 kilohertz blank and 147.20 kilohertz blank and 147.80 kilohertz blank and 152.00 kilohertz blank

Thread Size:

0.112 inches

Frequency Band Width Per Function:

147.20 kilohertz blank and 147.80 kilohertz blank

Discrimination At Specificationified Frequencies Per Function In Decibels:

30.0 blank and 1.0 blank and 1.0 blank and 30.0 blank

Maximum Dielectric Withstanding Dc Voltage:

100.0 volts at sea level

Style Designator:

Rectangular terminal/terminals on one surface

Test Data Document:

10001-2515586 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A047b0