

View Online at <https://aerobasegroup.com/nsn/5915-00-059-8884>

Overall Height:

Between 3.828 inches and 3.922 inches

Body Length:

Between 3.236 inches and 3.266 inches

Body Width:

Between 1.984 inches and 2.016 inches

Body Height:

Between 3.484 inches and 3.516 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

Between 2.609 inches and 2.641 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

Between 1.344 inches and 1.406 inches

Operating Temperature Range:

-55.0 to 71.0 degrees celsius

Reference Frequency Per Function:

9.75 kilohertz blank

Input Impedance Per Function W/load:

600.0 ohms blank

Output Impedance Per Function W/source Across Input:

600.0 ohms blank

Principal Circuitry Type Per Function:

Inductance-capacitance-resistance blank

Mounting Facility Screw Thread Series Designator:

Unc

Inclousure Type:

Hermetically sealed

Mounting Facility Type And Quantity:

4 threaded stud

Insertion Loss At Reference Frequency Per Function In Decibels:

1.0 blank

Functional Terminal Type And Quantity:

1 tab, solder lug output 2nd function

Maximum Dielectric Withstanding Ac Rms Voltage:

100.0 volts at sea level

Specified Frequencies Of Discrimination Per Function:

7.50 kilohertz blank and 8.30 kilohertz blank and 11.20 kilohertz blank and 12.30 kilohertz blank

Thread Size:

0.138 inches

Body Material:

Metal

Frequency Band Width Per Function:

8.30 kilohertz blank and 11.20 kilohertz blank

Discrimination At Specificationified Frequencies Per Function In Decibels:

40.0 blank and 1.5 blank and 1.5 blank and 40.0 blank

Unpackaged Unit Weight:

3.406 pounds

Style Designator:

Rectangular terminal/terminals on one surface

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A047b0