

View Online at <https://aerobasegroup.com/nsn/5915-00-060-9791>

Overall Height:

2.375 inches

Body Length:

1.938 inches

Body Width:

1.500 inches

Body Height:

2.000 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

1.000 inches

Vibration Resistance Range In Hertz:

+10.0 to 500.0

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

0.750 inches

Operating Temperature Range:

-55.0 to 75.0 degrees celsius

Reference Frequency Per Function:

2.15 kilohertz blank

Input Impedance Per Function W/load:

7.0 kilohms blank

Output Impedance Per Function W/source Across Input:

200.0 ohms blank

Mounting Facility Screw Thread Series Designator:

Unc

Inclosure Type:

Hermetically sealed

Mounting Facility Type And Quantity:

4 threaded stud

Insertion Loss At Reference Frequency Per Function In Decibels:

2.0 blank

Functional Terminal Type And Quantity:

2 tab, solder lug output 2nd function

Specified Frequencies Of Discrimination Per Function:

150.00 hertz blank and 300.00 hertz blank and 4.00 kilohertz blank and 14.00 kilohertz blank

Thread Size:

0.112 inches

Body Material:

Metal

Frequency Band Width Per Function:

300.00 hertz blank and 4.00 kilohertz blank

Discrimination At Specificationified Frequencies Per Function In Decibels:

30.0 blank and 2.0 blank and 2.0 blank and 20.0 blank

Style Designator:

Rectangular terminal/terminals on one surface

Test Data Document:

13499-673-0818-00 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A047b0