

View Online at <https://aerobasegroup.com/nsn/5915-00-061-6245>

Overall Length:

2.375 inches

Overall Height:

Between 2.188 inches and 2.312 inches

Overall Width:

Between 0.660 inches and 0.680 inches

Body Outside Diameter:

Between 0.432 inches and 0.442 inches

Body Height:

Between 1.604 inches and 1.696 inches

Unthreaded Mounting Hole Diameter:

0.123 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

Between 0.745 inches and 0.755 inches

Vibration Resistance Range In Hertz:

+10.0 to 55.0

Operating Temperature Range:

-30.0 to 80.0 degrees celsius

Reference Frequency Per Function:

500.0 kilohertz blank

Input Impedance Per Function W/load:

1.0 kilohms blank

Output Impedance Per Function W/source Across Input:

330.0 ohms blank

Distance Between Mounting Surface And Lower End:

Between 0.584 inches and 0.616 inches

Inclosure Type:

Hermetically sealed

Mounting Facility Type And Quantity:

2 unthreaded hole

Insertion Loss At Reference Frequency Per Function In Decibels:

3.0 blank

Functional Terminal Type And Quantity:

2 wire lead input 1st function

Specified Frequencies Of Discrimination Per Function:

490.50 kilohertz blank and 496.50 kilohertz blank and 503.50 kilohertz blank and 509.50 kilohertz blank

Body Material:

Metal

Frequency Band Width Per Function:

496.50 kilohertz blank and 503.50 kilohertz blank

Discrimination At Specificationified Frequencies Per Function In Decibels:

60.0 blank and 3.0 blank and 3.0 blank and 60.0 blank

Style Designator:

Round terminal/terminals on opposite surfaces

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A047b0