

View Online at <https://aerobasegroup.com/nsn/5915-00-064-9096>

Overall Height:

2.700 inches

Body Length:

4.000 inches

Body Width:

2.000 inches

Body Height:

1.500 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

3.000 inches

Vibration Resistance Range In Hertz:

+5.0 to 55.0

Operating Temperature Range:

+0.0 to 55.0 degrees celsius

Source Impedance Rating Per Function:

50.0 ohms 2nd radio interference 2nd function

Load Impedance Per Function:

50.0 ohms 2nd radio interference 2nd function

Power Line Frequency Rating Per Function In Hertz:

400.0 blank all functions

Operating Current Rating Per Function In Amps:

2.0 2nd radio interference 2nd function

Maximum Voltage Drop Per Function:

1.5 volts ac 1st radio interference 1st function

Principal Circuitry Type Per Function:

Inductance-capacitance 2nd radio interference 2nd function

Maximum Temperature Rise:

20.0 degrees celsius

Full Load Insertion Loss Frequencies In Megahertz:

0.15 and 1.0 and 10.0 and 100.0 and 200.0 and 400.0

Full Load Minimum Insertion Loss At Specificationified Frequency In Decibels:

75.0 and 100.0 and 100.0 and 100.0 and 90.0 and 90.0

Mounting Facility Screw Thread Series Designator:

Unc

Inclosure Type:

Hermetically sealed

Mounting Facility Type And Quantity:

2 threaded stud all functions

Features Provided:

Shock resistant and nut

Functional Terminal Type And Quantity:

2 threaded stud output 2nd function

Operating Voltage Rating And Type Per Function:

30.0 volts dc 2nd radio interference 2nd function

Thread Size:

0.164 inches

Body Material:

Metal

Maximum Dielectric Withstanding Dc Voltage:

500.0 volts at sea level

Special Features:

Two filtered functions

Style Designator:

Rectangular terminal/terminals on opposite surfaces

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A047b0