

View Online at <https://aerobasegroup.com/nsn/5915-00-067-9727>

Overall Height:

5.124 inches

Body Length:

3.938 inches

Body Width:

3.375 inches

Body Height:

4.562 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

3.000 inches

Vibration Resistance Range In Hertz:

+5.0 to 55.0

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

2.438 inches

Operating Temperature Range:

-40.0 to 70.0 degrees celsius

Average Life Rating In Hours:

250.0

Reference Frequency Per Function:

400.0 hertz blank

Source Impedance Rating Per Function:

2.0 ohms blank

Load Impedance Per Function:

110.0 ohms blank

Input Impedance Per Function W/load:

2.0 ohms blank

Output Impedance Per Function W/source Across Input:

110.0 ohms blank

Average Power Rating Per Function:

120.0 watts blank

Mounting Facility Screw Thread Series Designator:

Unf

Inclosure Type:

Hermetically sealed

Mounting Facility Type And Quantity:

4 threaded stud

Insertion Loss At Reference Frequency Per Function In Decibels:

3.0 blank

Functional Terminal Type And Quantity:

1 tab, solder lug output 2nd function

Specified Frequencies Of Discrimination Per Function:

340.00 hertz blank and 380.00 hertz blank and 420.00 hertz blank and 460.00 hertz blank

Thread Size:

0.190 inches

Body Material:

Metal

Frequency Band Width Per Function:

380.00 hertz blank and 420.00 hertz blank

Discrimination At Specificationified Frequencies Per Function In Decibels:

40.0 blank and 3.0 blank and 3.0 blank and 40.0 blank

Maximum Dielectric Withstanding Dc Voltage:

500.0 volts at sea level and 300.0 volts at altitude

Style Designator:

Rectangular terminal/terminals on one surface

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A047b0