

View Online at <https://aerobasegroup.com/nsn/5915-00-069-3876>

Overall Height:

0.750 inches

Body Length:

3.000 inches

Body Width:

2.180 inches

Body Height:

0.500 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

2.500 inches

Operating Temperature Range:

-28.0 to 65.0 degrees celsius

Reference Frequency Per Function:

1.9 kilohertz blank

Source Impedance Rating Per Function:

600.0 ohms blank

Load Impedance Per Function:

1.0 kilohms blank

Principal Circuitry Type Per Function:

Inductance-capacitance blank

Mounting Facility Screw Thread Series Designator:

Unc

Inclosure Type:

Encased

Mounting Facility Type And Quantity:

1 threaded hole

Insertion Loss At Reference Frequency Per Function In Decibels:

0.5 blank

Functional Terminal Type And Quantity:

1 pin output 2nd function

Maximum Dielectric Withstanding Ac Rms Voltage:

15.0 volts at sea level

Specified Frequencies Of Discrimination Per Function:

300.00 hertz blank and 3.50 kilohertz blank and 5.00 kilohertz blank and 20.00 kilohertz blank

Thread Size:

0.112 inches

Frequency Band Width Per Function:

300.00 hertz blank and 3.50 kilohertz blank

Discrimination At Specificationified Frequencies Per Function In Decibels:

0.5 blank and 0.5 blank and 25.0 blank and 25.0 blank

Style Designator:

Rectangular terminal/terminals on one surface

Test Data Document:

00724-08-00680-000 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A047b0