NSN 5915-00-069-5046

Band Pass Filter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5915-00-069-5046

Overall Height:
4.500 inches
Body Length:
2.250 inches
Body Width:
2.000 inches
Body Height:
4.000 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:
1.375 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
1.375 inches
Operating Tempurature Range:
+0.0 to 60.0 degrees celsius
Reference Frequency Per Function:
450.0 hertz blank
Input Impedance Per Function W/load:
600.0 ohms blank
Output Impedance Per Function W/source Across Input:
600.0 ohms blank
Mounting Facility Screw Thread Series Designator:
Unf
Unf Inclosure Type:
Inclosure Type:
Inclosure Type: Hermetically sealed
Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity:
Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity: 4 threaded stud
Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity: 4 threaded stud Insertion Loss At Reference Frequency Per Function In Decibels:
Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity: 4 threaded stud Insertion Loss At Reference Frequency Per Function In Decibels: 1.0 blank
Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity: 4 threaded stud Insertion Loss At Reference Frequency Per Function In Decibels: 1.0 blank Functional Terminal Type And Quantity:
Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity: 4 threaded stud Insertion Loss At Reference Frequency Per Function In Decibels: 1.0 blank Functional Terminal Type And Quantity: 2 pin ground 3rd function
Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity: 4 threaded stud Insertion Loss At Reference Frequency Per Function In Decibels: 1.0 blank Functional Terminal Type And Quantity: 2 pin ground 3rd function Specified Frequencies Of Discrimination Per Function:
Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity: 4 threaded stud Insertion Loss At Reference Frequency Per Function In Decibels: 1.0 blank Functional Terminal Type And Quantity: 2 pin ground 3rd function Specified Frequencies Of Discrimination Per Function: 110.00 hertz blank and 300.00 hertz blank and 600.00 hertz blank and 1.70 kilohertz blank
Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity: 4 threaded stud Insertion Loss At Reference Frequency Per Function In Decibels: 1.0 blank Functional Terminal Type And Quantity: 2 pin ground 3rd function Specified Frequencies Of Discrimination Per Function: 110.00 hertz blank and 300.00 hertz blank and 600.00 hertz blank and 1.70 kilohertz blank Thread Size:
Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity: 4 threaded stud Insertion Loss At Reference Frequency Per Function In Decibels: 1.0 blank Functional Terminal Type And Quantity: 2 pin ground 3rd function Specified Frequencies Of Discrimination Per Function: 110.00 hertz blank and 300.00 hertz blank and 600.00 hertz blank and 1.70 kilohertz blank Thread Size: 0.190 inches
Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity: 4 threaded stud Insertion Loss At Reference Frequency Per Function In Decibels: 1.0 blank Functional Terminal Type And Quantity: 2 pin ground 3rd function Specified Frequencies Of Discrimination Per Function: 110.00 hertz blank and 300.00 hertz blank and 600.00 hertz blank and 1.70 kilohertz blank Thread Size: 0.190 inches Body Material:
Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity: 4 threaded stud Insertion Loss At Reference Frequency Per Function In Decibels: 1.0 blank Functional Terminal Type And Quantity: 2 pin ground 3rd function Specified Frequencies Of Discrimination Per Function: 110.00 hertz blank and 300.00 hertz blank and 600.00 hertz blank and 1.70 kilohertz blank Thread Size: 0.190 inches Body Material: Metal
Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity: 4 threaded stud Insertion Loss At Reference Frequency Per Function In Decibels: 1.0 blank Functional Terminal Type And Quantity: 2 pin ground 3rd function Specified Frequencies Of Discrimination Per Function: 110.00 hertz blank and 300.00 hertz blank and 600.00 hertz blank and 1.70 kilohertz blank Thread Size: 0.190 inches Body Material: Metal Frequency Band Width Per Function:

Style Designator:

Rectangular terminal/terminals on one surface

NSN 5915-00-069-5046

Band Pass Filter - Page 2 of 2



Test Data Document:

80249-330697-2 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Shelf Life:

N/a

Unit Of Measure:

__

Demilitarization:

Yes - demil/mli

Fiig:

A047b0