## NSN 5915-00-069-9779

Low Pass Filter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5915-00-069-9779

Overall Height:
2.375 inches
Body Length:
1.625 inches
Body Width:
1.625 inches
Body Height:
2.375 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:
1.188 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
1.188 inches
Operating Tempurature Range:
+0.0 to 65.0 degrees celsius
Reference Frequency Per Function:
3.4 kilohertz blank
Source Impedance Rating Per Function:
1.0 kilohms blank
Load Impedance Per Function:
1.0 kilohms blank
Mounting Facility Screw Thread Series Designator:
Unc
Inclosure Type:
Hermetically sealed
Mounting Facility Type And Quantity:
Mounting Facility Type And Quantity: 4 threaded stud
4 threaded stud
4 threaded stud Insertion Loss At Reference Frequency Per Function In Decibels:
4 threaded stud  Insertion Loss At Reference Frequency Per Function In Decibels: 7.0 blank
4 threaded stud  Insertion Loss At Reference Frequency Per Function In Decibels: 7.0 blank  Functional Terminal Type And Quantity:
4 threaded stud  Insertion Loss At Reference Frequency Per Function In Decibels: 7.0 blank  Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function
4 threaded stud  Insertion Loss At Reference Frequency Per Function In Decibels: 7.0 blank  Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function  Specified Frequencies Of Discrimination Per Function:
4 threaded stud  Insertion Loss At Reference Frequency Per Function In Decibels: 7.0 blank  Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function  Specified Frequencies Of Discrimination Per Function: 3.05 kilohertz blank and 3.75 kilohertz blank and 8.20 kilohertz blank and 40.00 kilohertz blank
4 threaded stud  Insertion Loss At Reference Frequency Per Function In Decibels: 7.0 blank  Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function  Specified Frequencies Of Discrimination Per Function: 3.05 kilohertz blank and 3.75 kilohertz blank and 8.20 kilohertz blank and 40.00 kilohertz blank  Thread Size:
4 threaded stud  Insertion Loss At Reference Frequency Per Function In Decibels: 7.0 blank  Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function  Specified Frequencies Of Discrimination Per Function: 3.05 kilohertz blank and 3.75 kilohertz blank and 8.20 kilohertz blank and 40.00 kilohertz blank  Thread Size: 0.164 inches
4 threaded stud  Insertion Loss At Reference Frequency Per Function In Decibels: 7.0 blank  Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function  Specified Frequencies Of Discrimination Per Function: 3.05 kilohertz blank and 3.75 kilohertz blank and 8.20 kilohertz blank and 40.00 kilohertz blank  Thread Size: 0.164 inches  Frequency Band Width Per Function:
Insertion Loss At Reference Frequency Per Function In Decibels: 7.0 blank Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Specified Frequencies Of Discrimination Per Function: 3.05 kilohertz blank and 3.75 kilohertz blank and 8.20 kilohertz blank and 40.00 kilohertz blank Thread Size: 0.164 inches Frequency Band Width Per Function: 3.05 kilohertz blank and 3.75 kilohertz blank
Insertion Loss At Reference Frequency Per Function In Decibels: 7.0 blank  Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function  Specified Frequencies Of Discrimination Per Function: 3.05 kilohertz blank and 3.75 kilohertz blank and 8.20 kilohertz blank and 40.00 kilohertz blank  Thread Size: 0.164 inches  Frequency Band Width Per Function: 3.05 kilohertz blank and 3.75 kilohertz blank  Discrimination At Specificationified Frequencies Per Function In Decibels:

N/a

Shelf Life:

## NSN 5915-00-069-9779

Low Pass Filter - Page 2 of 2



		eas	

--

Demilitarization:

No

Fiig:

A047b0