NSN 5915-00-069-9779

Low Pass Filter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5915-00-069-9779

| Overall Height: |
|--|
| 2.375 inches |
| Body Length: |
| 1.625 inches |
| Body Width: |
| 1.625 inches |
| Body Height: |
| 2.375 inches |
| Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: |
| 1.188 inches |
| Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: |
| 1.188 inches |
| Operating Tempurature Range: |
| +0.0 to 65.0 degrees celsius |
| Reference Frequency Per Function: |
| 3.4 kilohertz blank |
| Source Impedance Rating Per Function: |
| 1.0 kilohms blank |
| Load Impedance Per Function: |
| 1.0 kilohms blank |
| Mounting Facility Screw Thread Series Designator: |
| Unc |
| Inclosure Type: |
| Hermetically sealed |
| |
| Mounting Facility Type And Quantity: |
| Mounting Facility Type And Quantity: 4 threaded stud |
| |
| 4 threaded stud |
| 4 threaded stud Insertion Loss At Reference Frequency Per Function In Decibels: |
| 4 threaded stud Insertion Loss At Reference Frequency Per Function In Decibels: 7.0 blank |
| 4 threaded stud Insertion Loss At Reference Frequency Per Function In Decibels: 7.0 blank Functional Terminal Type And Quantity: |
| 4 threaded stud Insertion Loss At Reference Frequency Per Function In Decibels: 7.0 blank Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function |
| 4 threaded stud Insertion Loss At Reference Frequency Per Function In Decibels: 7.0 blank Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Specified Frequencies Of Discrimination Per Function: |
| 4 threaded stud Insertion Loss At Reference Frequency Per Function In Decibels: 7.0 blank Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Specified Frequencies Of Discrimination Per Function: 3.05 kilohertz blank and 3.75 kilohertz blank and 8.20 kilohertz blank and 40.00 kilohertz blank |
| 4 threaded stud Insertion Loss At Reference Frequency Per Function In Decibels: 7.0 blank Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Specified Frequencies Of Discrimination Per Function: 3.05 kilohertz blank and 3.75 kilohertz blank and 8.20 kilohertz blank and 40.00 kilohertz blank Thread Size: |
| 4 threaded stud Insertion Loss At Reference Frequency Per Function In Decibels: 7.0 blank Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Specified Frequencies Of Discrimination Per Function: 3.05 kilohertz blank and 3.75 kilohertz blank and 8.20 kilohertz blank and 40.00 kilohertz blank Thread Size: 0.164 inches |
| 4 threaded stud Insertion Loss At Reference Frequency Per Function In Decibels: 7.0 blank Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Specified Frequencies Of Discrimination Per Function: 3.05 kilohertz blank and 3.75 kilohertz blank and 8.20 kilohertz blank and 40.00 kilohertz blank Thread Size: 0.164 inches Frequency Band Width Per Function: |
| Insertion Loss At Reference Frequency Per Function In Decibels: 7.0 blank Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Specified Frequencies Of Discrimination Per Function: 3.05 kilohertz blank and 3.75 kilohertz blank and 8.20 kilohertz blank and 40.00 kilohertz blank Thread Size: 0.164 inches Frequency Band Width Per Function: 3.05 kilohertz blank and 3.75 kilohertz blank |
| Insertion Loss At Reference Frequency Per Function In Decibels: 7.0 blank Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Specified Frequencies Of Discrimination Per Function: 3.05 kilohertz blank and 3.75 kilohertz blank and 8.20 kilohertz blank and 40.00 kilohertz blank Thread Size: 0.164 inches Frequency Band Width Per Function: 3.05 kilohertz blank and 3.75 kilohertz blank Discrimination At Specificationified Frequencies Per Function In Decibels: |

N/a

Shelf Life:

NSN 5915-00-069-9779

Low Pass Filter - Page 2 of 2



| | | eas | |
|--|--|-----|--|

--

Demilitarization:

No

Fiig:

A047b0