

View Online at <https://aerobasegroup.com/nsn/5915-00-078-1817>

**Overall Height:**

Between 2.188 inches and 2.212 inches

**Body Length:**

Between 2.844 inches and 2.906 inches

**Body Width:**

Between 1.219 inches and 1.281 inches

**Body Height:**

Between 1.844 inches and 1.906 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:**

Between 2.359 inches and 2.391 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:**

Between 0.734 inches and 0.766 inches

**Operating Temperature Range:**

-40.0/+50.0 degrees celsius

**Reference Frequency Per Function:**

1.74 kilohertz blank

**Source Impedance Rating Per Function:**

500.0 ohms blank

**Load Impedance Per Function:**

500.0 ohms blank

**Principal Circuitry Type Per Function:**

Inductance-capacitance blank

**Mounting Facility Screw Thread Series Designator:**

Unc

**Inclosure Type:**

Encased

**Mounting Facility Type And Quantity:**

4 threaded stud

**Insertion Loss At Reference Frequency Per Function In Decibels:**

1.0 blank

**Functional Terminal Type And Quantity:**

2 tab, solder lug output 2nd function

**Specified Frequencies Of Discrimination Per Function:**

645.00 hertz blank and 1.42 kilohertz blank and 2.05 kilohertz blank and 2.83 kilohertz blank

**Thread Size:**

0.138 inches

**Body Material:**

Metal

**Frequency Band Width Per Function:**

1.425 kilohertz blank and 2.055 kilohertz blank

**Discrimination At Specificationified Frequencies Per Function In Decibels:**

60.0 blank and 1.0 blank and 1.0 blank and 60.0 blank

**Style Designator:**

Rectangular terminal/terminals on one surface

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A047b0