

View Online at <https://aerobasegroup.com/nsn/5915-00-078-3251>

**Overall Length:**

3.160 inches

**Body Length:**

2.630 inches

**Body Width:**

1.560 inches

**Body Height:**

1.870 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:**

2.125 inches

**Vibration Resistance Range In Hertz:**

+10.0 to 55.0

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:**

0.562 inches

**Operating Temperature Range:**

-55.0 to 65.0 degrees celsius

**Average Life Rating In Hours:**

10000.0

**Reference Frequency Per Function:**

50.0 hertz single low pass 2nd function

**Source Impedance Rating Per Function:**

1.2 kilohms single low pass 2nd function

**Input Impedance Per Function W/load:**

50.0 ohms blank

**Output Impedance Per Function W/source Across Input:**

2.4 kilohms single low pass 2nd function

**Principal Circuitry Type Per Function:**

Inductance-capacitance single low pass 2nd function

**Mounting Facility Screw Thread Series Designator:**

Unc

**Inclosure Type:**

Encased

**Mounting Facility Type And Quantity:**

2 threaded hole

**Insertion Loss At Reference Frequency Per Function In Decibels:**

6.0 single band pass

**Functional Terminal Type And Quantity:**

2 wire hook input 1st function

**Specified Frequencies Of Discrimination Per Function:**

1.00 hertz single low pass and 100.00 hertz single low pass and 1.19 kilohertz single low pass and 2.38 kilohertz single low pass

**Thread Size:**

0.138 inches

**Body Material:**

Metal

**Frequency Band Width Per Function:**

557.00 hertz single band pass and 637.00 hertz single band pass 1st function

**Discrimination At Specificationified Frequencies Per Function In Decibels:**

3.0 single low pass and 3.0 single low pass and 50.0 single low pass and 50.0 single low pass

**Style Designator:**

Rectangular terminal/terminals on opposite surfaces

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A047b0