

View Online at <https://aerobasegroup.com/nsn/5915-00-078-3255>

Overall Length:

3.160 inches

Body Length:

2.630 inches

Body Width:

1.560 inches

Body Height:

1.870 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

2.125 inches

Vibration Resistance Range In Hertz:

+10.0/+55.0

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

0.562 inches

Operating Temperature Range:

-55.0 to 65.0 degrees celsius

Average Life Rating In Hours:

10000.0

Reference Frequency Per Function:

50.0 hertz single low pass 2nd function

Source Impedance Rating Per Function:

1.2 kilohms single low pass 2nd function

Input Impedance Per Function W/load:

50.0 ohms blank

Output Impedance Per Function W/source Across Input:

2.4 kilohms single band pass 1st function

Principal Circuitry Type Per Function:

Inductance-capacitance single low pass 2nd function

Mounting Facility Screw Thread Series Designator:

Unc

Inclosure Type:

Encased

Mounting Facility Type And Quantity:

2 threaded hole

Insertion Loss At Reference Frequency Per Function In Decibels:

6.0 single band pass

Functional Terminal Type And Quantity:

2 wire hook input 1st function

Specified Frequencies Of Discrimination Per Function:

1.00 hertz single low pass and 100.00 hertz single low pass and 2.00 kilohertz single low pass and 4.00 kilohertz single low pass

Thread Size:

0.138 inches

Body Material:

Metal

Frequency Band Width Per Function:

1.236 kilohertz single band pass and 1.316 kilohertz single band pass 1st function

Discrimination At Specificationified Frequencies Per Function In Decibels:

3.0 blank and 3.0 blank and 50.0 blank and 50.0 blank

Style Designator:

Rectangular terminal/terminals on opposite surfaces

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A047b0