## NSN 5915-00-078-7315

Low Pass Filter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5915-00-078-7315						
Overall Length:						
1.125 inches						
Body Length:						
1.000 inches						
Body Width:						
0.812 inches						
Body Height:						
0.563 inches						
Unthreaded Mounting Hole Diameter:						
0.093 inches						
Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:						
0.444 inches						
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:						
0.562 inches						
Reference Frequency Per Function:						
2.5 kilohertz blank						
Input Impedance Per Function W/load:						
15.0 kilohms blank						
Output Impedance Per Function W/source Across Input:						
22.0 kilohms blank						
Inclosure Type:						
Hermetically sealed						
Mounting Facility Type And Quantity:						
4 unthreaded hole						
Insertion Loss At Reference Frequency Per Function In Decibels:						
6.0 blank						
Functional Terminal Type And Quantity:						
1 solder stud input 1st function						
Specified Frequencies Of Discrimination Per Function:						
2.40 kilohertz blank and 2.60 kilohertz blank and 5.20 kilohertz blank and 7.20 kilohertz blank						

#### **Body Material:**

Metal

#### **Frequency Band Width Per Function:**

2.40 kilohertz blank and 2.60 kilohertz blank

#### Discrimination At Specificationified Frequencies Per Function In Decibels:

6.0 blank and 6.0 blank and 20.0 blank and 20.0 blank

#### **Special Features:**

0.563 o/a height including mtg offset holes; terminals on one surface; unit non-repairable

#### **Style Designator:**

Rectangular terminal/terminals on opposite surfaces

### Shelf Life:

N/a

# NSN 5915-00-078-7315

Low Pass Filter - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

--

Demilitarization:

No

Fiig:

A047b0