

View Online at <https://aerobasegroup.com/nsn/5915-00-078-7854>

Overall Length:

Between 2.220 inches and 2.280 inches

Overall Height:

0.820 inches

Overall Width:

Between 1.970 inches and 2.030 inches

Body Length:

Between 2.220 inches and 2.280 inches

Body Width:

Between 1.970 inches and 2.030 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

Between 1.684 inches and 1.716 inches

Vibration Resistance Range In Hertz:

+10.0/+55.0

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

Between 1.484 inches and 1.516 inches

Operating Temperature Range:

-40.0 to 85.0 degrees celsius

Average Life Rating In Hours:

10000.0

Reference Frequency Per Function:

1.5 kilohertz blank

Source Impedance Rating Per Function:

600.0 ohms blank

Load Impedance Per Function:

600.0 ohms blank

Input Impedance Per Function W/load:

600.0 ohms blank

Output Impedance Per Function W/source Across Input:

600.0 ohms blank

Mounting Facility Screw Thread Series Designator:

Unc

Inclosure Type:

Encased

Mounting Facility Type And Quantity:

4 threaded hole

Insertion Loss At Reference Frequency Per Function In Decibels:

1.0 blank

Functional Terminal Type And Quantity:

1 wire lead input 1st function

Specified Frequencies Of Discrimination Per Function:

200.00 hertz blank and 1.125 kilohertz blank and 1.875 kilohertz blank and 4.50 kilohertz blank

Thread Size:

0.138 inches

Body Material:

Metal

Frequency Band Width Per Function:

1.125 kilohertz blank and 1.875 kilohertz blank

Discrimination At Specificationified Frequencies Per Function In Decibels:

20.0 blank and 1.0 blank and 1.0 blank and 20.0 blank

Maximum Dielectric Withstanding Dc Voltage:

100.0 volts at sea level

Special Features:

Terminals on one surface

Style Designator:

Rectangular terminal/terminals on opposite surfaces

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A047b0