NSN 5915-00-078-7855

Low Pass Filter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5915-00-078-7855

Overall Height:

0.820 inches

Body Length:

Between 2.470 inches and 2.530 inches

Body Width:

Between 1.530 inches and 1.590 inches

Body Height:

0.820 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

Between 1.984 inches and 2.016 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

Between 0.840 inches and 1.016 inches

Operating Tempurature Range:

-40.0 to 85.0 degrees celsius

Reference Frequency Per Function:

12.0 hertz blank

Source Impedance Rating Per Function:

10.0 kilohms blank

Load Impedance Per Function:

1.5 kilohms blank

Mounting Facility Screw Thread Series Designator:

Unc

Inclosure Type:

Encased

Mounting Facility Type And Quantity:

4 threaded hole

Insertion Loss At Reference Frequency Per Function In Decibels:

13.0 blank

Functional Terminal Type And Quantity:

1 wire lead input 1st function

Specified Frequencies Of Discrimination Per Function:

0.00 hertz blank and 60.00 hertz blank and 1.00 kilohertz blank and 1.00 kilohertz blank

Thread Size:

0.138 inches

Frequency Band Width Per Function:

0.00 hertz blank and 60.00 hertz blank

Discrimination At Specificationified Frequencies Per Function In Decibels:

0.0 blank and 2.5 blank and 55.0 blank and 55.0 blank

Maximum Dielectric Withstanding Dc Voltage:

100.0 volts at sea level

Style Designator:

Rectangular terminal/terminals on one surface

NSN 5915-00-078-7855

Low Pass Filter - Page 2 of 2



_			•		
•	n	ο.	•	18	e:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A047b0