## NSN 5915-00-078-7855

Low Pass Filter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5915-00-078-7855

**Overall Height:** 

0.820 inches

**Body Length:** 

Between 2.470 inches and 2.530 inches

**Body Width:** 

Between 1.530 inches and 1.590 inches

**Body Height:** 

0.820 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

Between 1.984 inches and 2.016 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

Between 0.840 inches and 1.016 inches

**Operating Tempurature Range:** 

-40.0 to 85.0 degrees celsius

**Reference Frequency Per Function:** 

12.0 hertz blank

**Source Impedance Rating Per Function:** 

10.0 kilohms blank

**Load Impedance Per Function:** 

1.5 kilohms blank

**Mounting Facility Screw Thread Series Designator:** 

Unc

**Inclosure Type:** 

Encased

**Mounting Facility Type And Quantity:** 

4 threaded hole

Insertion Loss At Reference Frequency Per Function In Decibels:

13.0 blank

**Functional Terminal Type And Quantity:** 

1 wire lead input 1st function

**Specified Frequencies Of Discrimination Per Function:** 

0.00 hertz blank and 60.00 hertz blank and 1.00 kilohertz blank and 1.00 kilohertz blank

Thread Size:

0.138 inches

**Frequency Band Width Per Function:** 

0.00 hertz blank and 60.00 hertz blank

Discrimination At Specificationified Frequencies Per Function In Decibels:

0.0 blank and 2.5 blank and 55.0 blank and 55.0 blank

**Maximum Dielectric Withstanding Dc Voltage:** 

100.0 volts at sea level

**Style Designator:** 

Rectangular terminal/terminals on one surface

## NSN 5915-00-078-7855

Low Pass Filter - Page 2 of 2



_			•		
•	n	ο.	•	18	e:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A047b0