## NSN 5915-00-080-6385

Band Pass Filter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5915-00-080-6385

| Overall Height:   |
|---|
| 2.312 inches  |
| Body Length:  |
| 1.531 inches  |
| Body Width:   |
| 0.500 inches  |
| Body Height:  |
| 1.859 inches  |
| Unthreaded Mounting Hole Diameter:  |
| 0.125 inches  |
| Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:                    |
| 1.312 inches  |
| Vibration Resistance Range In Hertz:  |
| +10.0 to 55.0   |
| Operating Tempurature Range:  |
| -55.0/+85.0 degrees celsius   |
| Average Life Rating In Hours:   |
| 10000.0   |
| Reference Frequency Per Function:   |
| 3.43 megahertz blank  |
| Source Impedance Rating Per Function:   |
| 600.0 ohms blank  |
| Load Impedance Per Function:  |
| 600.0 ohms blank  |
| Principal Circuitry Type Per Function:  |
| Inductance-capacitance blank  |
| Inclosure Type:   |
| Hermetically sealed   |
| Mounting Facility Type And Quantity:  |
| 2 threaded hole   |
| Insertion Loss At Reference Frequency Per Function In Decibels:                                 |
| 3.0 blank   |
| Functional Terminal Type And Quantity:  |
| 1 connector, receptacle output 2nd function   |
| Specified Frequencies Of Discrimination Per Function:   |
| 2.80 gigahertz blank and 3.05 gigahertz blank and 3.55 gigahertz blank and 3.75 gigahertz blank |
| Body Material:  |
| Metal   |
| Frequency Band Width Per Function:  |
| 3.05 megahertz blank and 3.55 megahertz blank   |

Discrimination At Specificationified Frequencies Per Function In Decibels:

3.0 blank and 40.0 blank

## NSN 5915-00-080-6385

Band Pass Filter - Page 2 of 2



Rectangular terminal/terminals on one surface

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A047b0