

View Online at <https://aerobasegroup.com/nsn/5915-00-080-8724>

Overall Length:

4.406 inches

Body Length:

2.906 inches

Body Width:

2.375 inches

Body Height:

1.303 inches

Unthreaded Mounting Hole Diameter:

Between 0.154 inches and 0.162 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

Between 4.000 inches and 4.016 inches

Vibration Resistance Range In Hertz:

+10.0/+55.0

Operating Temperature Range:

-55.0 to 105.0 degrees celsius

Source Impedance Rating Per Function:

50.0 ohms 1st radio interference 1st function 50.0 ohms 2nd radio interference 2nd function 50.0 ohms 3rd radio interference 50.0 ohms 4th radio interference

Load Impedance Per Function:

50.0 ohms 1st radio interference 50.0 ohms 2nd radio interference 50.0 ohms 3rd radio interference 50.0 ohms 4th radio interference 50.0 ohms 4th function

Operating Current Rating Per Function In Amps:

2.0 1st radio interference 1st function 2.0 2nd radio interference 2.0 3rd radio interference 2.0 4th radio interference

Maximum Voltage Drop Per Function:

1.5 volts dc 1st radio interference 1st function 1.5 volts dc 2nd radio interference 1.5 volts dc 3rd radio interference 1.5 volts dc 4th radio interference 4th function

Principal Circuitry Type Per Function:

Inductance-capacitance 1st radio interference inductance-capacitance 2nd radio interference inductance-capacitance 3rd radio interference 3rd function inductance-capacitance 4th radio interference 4th function

Inclosure Type:

Hermetically sealed

Mounting Facility Type And Quantity:

2 unthreaded hole

Features Provided:

Mounting bracket

Functional Terminal Type And Quantity:

4 tab, solder lug input 1st function 4 tab, solder lug output 2nd function 3 tab, solder lug ground 3rd function

Operating Voltage Rating And Type Per Function:

150.0 volts dc 1st radio interference 1st function 150.0 volts dc 2nd radio interference 2nd function 150.0 volts dc 3rd radio interference 3rd function 150.0 volts dc 4th radio interference 4th function

Body Material:

Metal

Maximum Dielectric Withstanding Dc Voltage:

300.0 volts at sea level

Style Designator:

Rectangular terminal/terminals on opposite surfaces

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A047b0