## NSN 5915-00-084-3496

High Pass Filter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5915-00-084-3496

**Overall Height:** 

3.501 inches

**Body Length:** 

Between 2.938 inches and 3.095 inches

**Body Width:** 

Between 1.562 inches and 1.657 inches

**Body Height:** 

Between 2.938 inches and 3.095 inches

**Unthreaded Mounting Hole Diameter:** 

Between 0.196 inches and 0.203 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:** 

3.625 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

0.938 inches

**Operating Tempurature Range:** 

-55.0/+85.0 degrees celsius

**Reference Frequency Per Function:** 

500.0 hertz blank

**Source Impedance Rating Per Function:** 

1.0 kilohms blank

**Load Impedance Per Function:** 

1.0 kilohms blank

**Principal Circuitry Type Per Function:** 

Inductance-capacitance blank

**Inclosure Type:** 

Hermetically sealed

**Mounting Facility Type And Quantity:** 

4 unthreaded hole

Insertion Loss At Reference Frequency Per Function In Decibels:

3.0 blank

**Functional Terminal Type And Quantity:** 

2 turret ground 3rd function

**Specified Frequencies Of Discrimination Per Function:** 

200.00 hertz blank and 350.00 hertz blank and 500.00 hertz blank and 700.00 hertz blank

**Body Material:** 

Metal

**Frequency Band Width Per Function:** 

500.00 hertz blank and 700.00 hertz blank

Discrimination At Specificationified Frequencies Per Function In Decibels:

3.0 blank and 60.0 blank

**Special Features:** 

Matched pair

## NSN 5915-00-084-3496

High Pass Filter - Page 2 of 2



Sty	le	De	siq	ına	ato	r:
,	_			,		

Rectangular terminal/terminals on one surface

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A047b0