

View Online at <https://aerobasegroup.com/nsn/5915-00-085-0186>

**Overall Height:**

Between 2.130 inches and 2.250 inches

**Body Length:**

Between 2.440 inches and 2.560 inches

**Body Width:**

Between 0.720 inches and 0.780 inches

**Body Height:**

Between 1.940 inches and 2.060 inches

**Unthreaded Mounting Hole Diameter:**

Between 0.177 inches and 0.197 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:**

Between 2.045 inches and 2.075 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:**

Between 1.165 inches and 1.195 inches

**Operating Temperature Range:**

-65.0 to 85.0 degrees fahrenheit

**Average Life Rating In Hours:**

250.0

**Source Impedance Rating Per Function:**

50.0 ohms 3rd radio interference 3rd function

**Load Impedance Per Function:**

50.0 ohms 4th radio interference 4th function

**Operating Current Rating Per Function In Amps:**

0.5 4th radio interference 4th function

**Maximum Voltage Drop Per Function:**

150.0 millivolts dc 4th radio interference 4th function

**Principal Circuitry Type Per Function:**

Inductance-capacitance 3rd radio interference 3rd function

**Inclosure Type:**

Encased

**Mounting Facility Type And Quantity:**

4 unthreaded hole

**Functional Terminal Type And Quantity:**

1 connector, receptacle input-output/ground

**Operating Voltage Rating And Type Per Function:**

28.0 volts dc 1st radio interference 1st function

**Maximum Dielectric Withstanding Dc Voltage:**

200.0 volts at sea level

**Special Features:**

1.470 in. Min, 1.530 in. Maximum o/a width

**Style Designator:**

Rectangular terminal/terminals on one surface

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A047b0