

View Online at <https://aerobasegroup.com/nsn/5915-00-087-5858>

Overall Length:

2.812 inches

Overall Height:

1.062 inches

Body Length:

2.406 inches

Body Width:

0.500 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

2.550 inches

Vibration Resistance Range In Hertz:

+5.0 to 500.0

Operating Temperature Range:

-62.0 to 90.0 degrees celsius

Reference Frequency Per Function:

364.1 kilohertz blank

Source Impedance Rating Per Function:

1.5 kilohms blank

Load Impedance Per Function:

1.0 kilohms blank

Input Impedance Per Function W/load:

1.5 kilohms blank

Output Impedance Per Function W/source Across Input:

1.0 kilohms blank

Principal Circuitry Type Per Function:

Inductance-capacitance blank

Mounting Facility Screw Thread Series Designator:

Unc

Inclosure Type:

Hermetically sealed

Mounting Facility Type And Quantity:

2 threaded hole

Insertion Loss At Reference Frequency Per Function In Decibels:

3.0 blank

Functional Terminal Type And Quantity:

2 pin ground 3rd function

Specified Frequencies Of Discrimination Per Function:

160.91 kilohertz blank and 360.91 kilohertz blank and 367.29 kilohertz blank and 560.91 kilohertz blank

Thread Size:

0.112 inches

Body Material:

Metal

Frequency Band Width Per Function:

360.91 kilohertz blank and 367.29 kilohertz blank

Discrimination At Specificationified Frequencies Per Function In Decibels:

60.0 blank and 3.0 blank and 3.0 blank and 60.0 blank

Style Designator:

Rectangular terminal/terminals on adjacent surfaces

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A047b0