## NSN 5915-00-101-2206

Band Pass Filter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5915-00-101-2206

Overall Height:
1.262 inches
Body Length:
1.250 inches
Body Width:
1.000 inches
Body Height:
0.950 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:
0.688 inches
Vibration Resistance Range In Hertz:
+10.0 to 55.0
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
0.938 inches
Operating Tempurature Range:
-30.0 to 65.0 degrees celsius
Average Life Rating In Hours:
10000.0
Reference Frequency Per Function:
11.5 megahertz blank
Source Impedance Rating Per Function:
50.0 ohms blank
Load Impedance Per Function:
50.0 ohms blank
Principal Circuitry Type Per Function:
Crystal blank
Mounting Facility Screw Thread Series Designator:
Unc
Inclosure Type:
Hermetically sealed
Mounting Facility Type And Quantity:
4 threaded stud
Insertion Loss At Reference Frequency Per Function In Decibels:
5.0 blank
Functional Terminal Type And Quantity:
1 pin output 2nd function
Specified Frequencies Of Discrimination Per Function:
11.455 megahertz blank and 11.48 megahertz blank and 11.52 megahertz blank and 11.545 megahertz blank
Thread Size:
0.112 inches
Frequency Band Width Per Function:

11.48 megahertz blank and 11.52 megahertz blank

## NSN 5915-00-101-2206

Band Pass Filter - Page 2 of 2



## Discrimination At Specificationified Frequencies Per Function In Decibels:

60.0 blank and 3.0 blank and 60.0 blank

**Style Designator:** 

Rectangular terminal/terminals on one surface

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A047b0