

View Online at <https://aerobasegroup.com/nsn/5915-00-103-0275>

**Overall Height:**

1.420 inches

**Body Length:**

2.000 inches

**Body Width:**

1.000 inches

**Body Height:**

1.000 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:**

1.600 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:**

0.600 inches

**Operating Temperature Range:**

-0.0 to 60.0 degrees celsius

**Reference Frequency Per Function:**

469.751 kilohertz 2nd band pass 2nd function

**Source Impedance Rating Per Function:**

2.2 kilohms 2nd band pass 2nd function

**Load Impedance Per Function:**

2.2 kilohms 2nd band pass 2nd function

**Principal Circuitry Type Per Function:**

Crystal 2nd band pass 2nd function

**Mounting Facility Screw Thread Series Designator:**

Unc

**Inclosure Type:**

Hermetically sealed

**Mounting Facility Type And Quantity:**

2 threaded stud

**Insertion Loss At Reference Frequency Per Function In Decibels:**

3.5 1st band pass 1st function

**Functional Terminal Type And Quantity:**

3 pin ground 3rd function

**Maximum Dielectric Withstanding Ac Rms Voltage:**

50.0 volts at sea level

**Specificationified Frequencies Of Discrimination Per Function:**

469.501 kilohertz 1st band pass and 469.726 kilohertz 1st band pass and 469.776 kilohertz 1st band pass and 470.001 kilohertz 1st band pass 1st function

**Thread Size:**

0.112 inches

**Body Material:**

Metal

**Frequency Band Width Per Function:**

469.726 kilohertz 2nd band pass and 469.776 kilohertz 2nd band pass

**Discrimination At Specificationified Frequencies Per Function In Decibels:**

20.0 2nd band pass 2nd function and 3.0 2nd band pass 2nd function and 3.0 2nd band pass 2nd function and 20.0 2nd band pass 2nd function

**Style Designator:**

Rectangular terminal/terminals on one surface

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A047b0