

View Online at <https://aerobasegroup.com/nsn/5915-00-103-0275>

Overall Height:

1.420 inches

Body Length:

2.000 inches

Body Width:

1.000 inches

Body Height:

1.000 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

1.600 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

0.600 inches

Operating Temperature Range:

-0.0 to 60.0 degrees celsius

Reference Frequency Per Function:

469.751 kilohertz 2nd band pass 2nd function

Source Impedance Rating Per Function:

2.2 kilohms 2nd band pass 2nd function

Load Impedance Per Function:

2.2 kilohms 2nd band pass 2nd function

Principal Circuitry Type Per Function:

Crystal 2nd band pass 2nd function

Mounting Facility Screw Thread Series Designator:

Unc

Inclosure Type:

Hermetically sealed

Mounting Facility Type And Quantity:

2 threaded stud

Insertion Loss At Reference Frequency Per Function In Decibels:

3.5 1st band pass 1st function

Functional Terminal Type And Quantity:

3 pin ground 3rd function

Maximum Dielectric Withstanding Ac Rms Voltage:

50.0 volts at sea level

Specificationifed Frequencies Of Discrimination Per Function:

469.501 kilohertz 1st band pass and 469.726 kilohertz 1st band pass and 469.776 kilohertz 1st band pass and 470.001 kilohertz 1st band pass 1st function

Thread Size:

0.112 inches

Body Material:

Metal

Frequency Band Width Per Function:

469.726 kilohertz 2nd band pass and 469.776 kilohertz 2nd band pass

Discrimination At Specificationified Frequencies Per Function In Decibels:

20.0 2nd band pass 2nd function and 3.0 2nd band pass 2nd function and 3.0 2nd band pass 2nd function and 20.0 2nd band pass 2nd function

Style Designator:

Rectangular terminal/terminals on one surface

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A047b0