

View Online at <https://aerobasegroup.com/nsn/5915-00-103-1656>

Overall Height:

1.240 inches

Body Length:

4.000 inches

Body Width:

2.500 inches

Body Height:

1.000 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

Between 3.182 inches and 3.192 inches

Vibration Resistance Range In Hertz:

+10.0 to 55.0

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

Between 1.745 inches and 1.755 inches

Operating Temperature Range:

-55.0 to 70.0 degrees celsius

Reference Frequency Per Function:

27.5 hertz blank

Source Impedance Rating Per Function:

10.0 kilohms blank

Load Impedance Per Function:

10.0 kilohms blank

Input Impedance Per Function W/load:

10.0 kilohms blank

Output Impedance Per Function W/source Across Input:

10.0 kilohms blank

Mounting Facility Screw Thread Series Designator:

Unc

Inclosure Type:

Hermetically sealed

Mounting Facility Type And Quantity:

4 threaded stud

Insertion Loss At Reference Frequency Per Function In Decibels:

1.5 blank

Functional Terminal Type And Quantity:

2 tab, solder lug ground 3rd function

Maximum Dielectric Withstanding Ac Rms Voltage:

500.0 volts at sea level

Specified Frequencies Of Discrimination Per Function:

10.00 hertz blank and 45.00 hertz blank and 300.00 hertz blank and 500.00 hertz blank

Thread Size:

0.138 inches

Frequency Band Width Per Function:

10.00 hertz blank and 45.00 hertz blank

Discrimination At Specificationified Frequencies Per Function In Decibels:

7.0 blank and 7.0 blank and 120.0 blank and 122.0 blank

Style Designator:

Rectangular terminal/terminals on one surface

Test Data Document:

13499-673-1152-010 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excluzes any specification, standard or other document that may be referenced in a basic governing drawing)

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A047b0