## NSN 5915-00-107-2574

Low Pass Filter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5915-00-107-2574

| Overall Height:  |
|--|
| 1.200 inches   |
| Body Length:   |
| 3.500 inches   |
| Body Width:  |
| 0.610 inches   |
| Body Height:   |
| 0.950 inches   |
| Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:                   |
| 3.100 inches   |
| Vibration Resistance Range In Hertz:   |
| +10.0 to 500.0   |
| Operating Tempurature Range:   |
| -55.0 to 100.0 degrees celsius   |
| Reference Frequency Per Function:  |
| 500.0 hertz blank  |
| Source Impedance Rating Per Function:  |
| 1.0 kilohms blank  |
| Load Impedance Per Function:   |
| 2.0 kilohms blank  |
| Mounting Facility Screw Thread Series Designator:  |
| Unc  |
| Inclosure Type:  |
| Hermetically sealed  |
| Mounting Facility Type And Quantity:   |
| 2 threaded hole  |
| Insertion Loss At Reference Frequency Per Function In Decibels:                                |
| 4.5 blank  |
| Functional Terminal Type And Quantity:   |
| 2 tab, solder lug output 2nd function  |
| Specified Frequencies Of Discrimination Per Function:  |
| 0.00 hertz blank and 1.00 kilohertz blank and 40.00 kilohertz blank and 120.00 kilohertz blank |
| Thread Size:   |
| 0.112 inches   |
| Frequency Band Width Per Function:   |
| 0.00 hertz blank and 1.00 kilohertz blank  |
| Discrimination At Specificationified Frequencies Per Function In Decibels:                     |
| 3.0 blank and 3.0 blank and 115.0 blank and 115.0 blank  |
| Style Designator:  |
| Rectangular terminal/terminals on one surface  |

N/a

Shelf Life:

## NSN 5915-00-107-2574

Low Pass Filter - Page 2 of 2



|  |  | eas |  |
|--|--|-----|--|
|  |  |     |  |

--

Demilitarization:

No

Fiig:

A047b0