

View Online at <https://aerobasegroup.com/nsn/5915-00-115-3633>

Overall Height:

2.923 inches

Body Length:

2.500 inches

Body Width:

0.500 inches

Body Height:

1.938 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

2.160 inches

Vibration Resistance Range In Hertz:

+10.0 to 500.0

Operating Temperature Range:

-55.0 to 125.0 degrees celsius

Reference Frequency Per Function:

65.0 megahertz 2nd low pass 2nd function

Source Impedance Rating Per Function:

50.0 ohms 2nd low pass 2nd function

Load Impedance Per Function:

50.0 ohms 2nd low pass 2nd function

Voltage Standing Wave Ratio Per Function:

1.3 2nd low pass 2nd function

Average Power Rating Per Function:

30.0 watts 2nd low pass 2nd function

Mounting Facility Screw Thread Series Designator:

Unc

Inclosure Type:

Encased

Mounting Facility Type And Quantity:

3 threaded stud

Insertion Loss At Reference Frequency Per Function In Decibels:

0.4 1st low pass 1st function

Functional Terminal Type And Quantity:

2 pin output 2nd function

Specified Frequencies Of Discrimination Per Function:

30.00 megahertz 1st low pass and 48.00 megahertz 1st low pass and 60.00 megahertz 1st low pass and 90.00 megahertz 1st low pass

Thread Size:

0.112 inches

Body Material:

Metal

Frequency Band Width Per Function:

30.00 megahertz 2nd low pass and 76.00 megahertz 2nd low pass 2nd function

Discrimination At Specificationified Frequencies Per Function In Decibels:

1.0 2nd low pass and 1.0 2nd low pass and 60.0 2nd low pass and 60.0 2nd low pass

Special Features:

0/a @w 0.750 @in. Max

Style Designator:

Rectangular terminal/terminals on one surface

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A047b0