

View Online at <https://aerobasegroup.com/nsn/5915-00-118-2602>

Overall Height:

1.437 inches

Body Length:

3.000 inches

Body Width:

1.000 inches

Body Height:

1.125 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

2.626 inches

Vibration Resistance Range In Hertz:

+10.0 to 55.0

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

0.625 inches

Operating Temperature Range:

+0.0/+65.0 degrees celsius

Average Life Rating In Hours:

10000.0

Reference Frequency Per Function:

15.11 megahertz blank

Source Impedance Rating Per Function:

150.0 ohms blank

Input Impedance Per Function W/load:

150.0 ohms blank

Output Impedance Per Function W/source Across Input:

150.0 ohms blank

Principal Circuitry Type Per Function:

Crystal blank

Mounting Facility Screw Thread Series Designator:

Unc

Inclosure Type:

Encased

Mounting Facility Type And Quantity:

1 threaded stud

Insertion Loss At Reference Frequency Per Function In Decibels:

6.0 blank

Functional Terminal Type And Quantity:

1 wire hook output 2nd function

Maximum Dielectric Withstanding Ac Rms Voltage:

100.0 volts at sea level

Specified Frequencies Of Discrimination Per Function:

15.105 megahertz blank and 15.109 megahertz blank and 15.111 megahertz blank and 15.115 megahertz blank

Thread Size:

0.112 inches

Frequency Band Width Per Function:

15.109 megahertz blank and 15.111 megahertz blank

Discrimination At Specificationified Frequencies Per Function In Decibels:

60.0 blank and 1.0 blank and 1.0 blank and 60.0 blank

Style Designator:

Rectangular terminal/terminals on one surface

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A047b0