AeroBase Group

View Online at https://aerobasegroup.com/nsn/5915-00-119-9104

View Online at https://aerobasegroup.com/nsn/5915-00-119-9104
Overall Length:
2.437 inches
Body Length:
1.750 inches
Body Outside Diameter:
0.750 inches
Operating Tempurature Range:
-55.0 to 85.0 degrees celsius
Average Life Rating In Hours:
250.0
Source Impedance Rating Per Function:
50.0 ohms blank
Load Impedance Per Function:
50.0 ohms blank
Power Line Frequency Rating Per Function In Hertz:
400.0 blank
Operating Current Rating Per Function In Amps:
2.5 blank
Principal Circuitry Type Per Function:
Inductance-capacitance-resistance blank
Mounting Facility Screw Thread Series Designator:
Unf
Inclosure Type:
Encased
Mounting Facility Type And Quantity:
1 threaded bushing
1 threaded bushing Functional Terminal Type And Quantity:
Functional Terminal Type And Quantity:
Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function
Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Maximum Dielectric Withstanding Ac Rms Voltage:
 Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Maximum Dielectric Withstanding Ac Rms Voltage: 250.0 volts at sea level
 Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Maximum Dielectric Withstanding Ac Rms Voltage: 250.0 volts at sea level Operating Voltage Rating And Type Per Function:
 Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Maximum Dielectric Withstanding Ac Rms Voltage: 250.0 volts at sea level Operating Voltage Rating And Type Per Function: 125.0 volts ac blank
Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Maximum Dielectric Withstanding Ac Rms Voltage: 250.0 volts at sea level Operating Voltage Rating And Type Per Function: 125.0 volts ac blank Thread Size:
Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Maximum Dielectric Withstanding Ac Rms Voltage: 250.0 volts at sea level Operating Voltage Rating And Type Per Function: 125.0 volts ac blank Thread Size: 0.312 inches
Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Maximum Dielectric Withstanding Ac Rms Voltage: 250.0 volts at sea level Operating Voltage Rating And Type Per Function: 125.0 volts ac blank Thread Size: 0.312 inches Body Material:
Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Maximum Dielectric Withstanding Ac Rms Voltage: 250.0 volts at sea level Operating Voltage Rating And Type Per Function: 125.0 volts ac blank Thread Size: 0.312 inches Body Material: Metal
Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Maximum Dielectric Withstanding Ac Rms Voltage: 250.0 volts at sea level Operating Voltage Rating And Type Per Function: 125.0 volts ac blank Thread Size: 0.312 inches Body Material: Metal Body Surface Treatment:
Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Maximum Dielectric Withstanding Ac Rms Voltage: 250.0 volts at sea level Operating Voltage Rating And Type Per Function: 125.0 volts ac blank Thread Size: 0.312 inches Body Material: Metal Body Surface Treatment: Tin
Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Maximum Dielectric Withstanding Ac Rms Voltage: 250.0 volts at sea level Operating Voltage Rating And Type Per Function: 125.0 volts ac blank Thread Size: 0.312 inches Body Material: Metal Body Surface Treatment: Tin Style Designator:

12464-b46n0025 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Radio Frequency Interference Filter - Page 2 of 2



Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A047b0