

View Online at <https://aerobasegroup.com/nsn/5915-00-121-5544>

Overall Height:

1.750 inches

Body Length:

1.000 inches

Body Width:

1.000 inches

Body Height:

1.375 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

0.750 inches

Vibration Resistance Range In Hertz:

+10.0 to 2000.0

Operating Temperature Range:

-55.0 to 105.0 degrees celsius

Average Life Rating In Hours:

10000.0

Reference Frequency Per Function:

500.0 hertz blank

Source Impedance Rating Per Function:

10.0 kilohms blank

Load Impedance Per Function:

10.0 kilohms blank

Principal Circuitry Type Per Function:

Inductance-capacitance blank

Mounting Facility Screw Thread Series Designator:

Unc

Inclosure Type:

Hermetically sealed

Mounting Facility Type And Quantity:

2 threaded stud

Insertion Loss At Reference Frequency Per Function In Decibels:

2.0 blank

Functional Terminal Type And Quantity:

1 wire lead input 1st function

Specified Frequencies Of Discrimination Per Function:

1.00 hertz blank and 1.00 kilohertz blank and 1.50 kilohertz blank and 2.00 kilohertz blank

Thread Size:

0.112 inches

Body Material:

Metal

Frequency Band Width Per Function:

1.00 hertz blank and 1.00 kilohertz blank

Discrimination At Specificationified Frequencies Per Function In Decibels:

6.0 blank and 6.0 blank and 30.0 blank and 40.0 blank

Body Surface Treatment:

Tin

Unpackaged Unit Weight:

2.250 ounces

Style Designator:

Rectangular terminal/terminals on one surface

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A047b0