## NSN 5915-00-126-4705

Band Pass Filter - Page 1 of 2



view Online at https://aerobasegroup.com/nsn/5915-00-126-4705
Overall Height:
2.375 inches
Body Length:
3.000 inches
Body Width:
1.000 inches
Body Height:
2.000 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:
2.562 inches
Vibration Resistance Range In Hertz:
+10.0 to 55.0
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
0.500 inches
Operating Tempurature Range:
+0.0/+70.0 degrees celsius
Average Life Rating In Hours:
1000.0
Reference Frequency Per Function:
1.281 megahertz blank
Input Impedance Per Function W/load:
5.0 kilohms blank
Output Impedance Per Function W/source Across Input:
25.0 kilohms blank
Principal Circuitry Type Per Function:
Crystal blank
Mounting Facility Screw Thread Series Designator:
Unc
Inclosure Type:
Hermetically sealed
Mounting Facility Type And Quantity:
1 threaded stud 1st function
Insertion Loss At Reference Frequency Per Function In Decibels:
1.0 blank
Functional Terminal Type And Quantity:
1 wire hook output 2nd function
Specified Frequencies Of Discrimination Per Function:
860.00 kilohertz blank and 1.146 megahertz blank and 1.416 megahertz blank and 1.70 megahertz blank
Thread Size:
0.112 inches
Frequency Band Width Per Function:

1.146 megahertz blank and 1.416 megahertz blank

## NSN 5915-00-126-4705

Band Pass Filter - Page 2 of 2



<b>Discrimination At Speci</b>	ficationified Frequ	ıencies Per Fu	ınction In Decibels:
--------------------------------	---------------------	----------------	----------------------

40.0 blank and 3.0 blank and 40.0 blank

**Style Designator:** 

Rectangular terminal/terminals on one surface

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

Yes - demil/mli

Fiig:

A047b0