NSN 5915-00-126-5956

Band Pass Filter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5915-00-126-5956

| Overall Height: |
|---|
| 1.110 inches |
| Body Length: |
| 2.380 inches |
| Body Width: |
| 1.032 inches |
| Body Height: |
| 0.800 inches |
| Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: |
| 1.936 inches |
| Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: |
| 0.562 inches |
| Operating Tempurature Range: |
| -54.0/+70.0 degrees celsius |
| Reference Frequency Per Function: |
| 20.6 megahertz blank |
| Input Impedance Per Function W/load: |
| 50.0 ohms blank |
| Output Impedance Per Function W/source Across Input: |
| 50.0 ohms blank |
| Principal Circuitry Type Per Function: |
| Crystal blank |
| Mounting Facility Screw Thread Series Designator: |
| Unc |
| Inclosure Type: |
| Encased |
| Mounting Facility Type And Quantity: |
| 2 threaded stud |
| Insertion Loss At Reference Frequency Per Function In Decibels: |
| 4.0 blank |
| Functional Terminal Type And Quantity: |
| 1 connector, plug output 2nd function |
| Specified Frequencies Of Discrimination Per Function: |
| $20.54 \ megahertz \ blank \ and \ 20.57 \ megahertz \ blank \ and \ 20.63 \ megahertz \ blank \ and \ 20.66 \ megahertz \ blank$ |
| Thread Size: |
| 0.112 inches |
| Frequency Band Width Per Function: |
| 20.57 megahertz blank and 20.63 megahertz blank |
| Discrimination At Specificationified Frequencies Per Function In Decibels: |
| 100.0 blank and 20.0 blank and 20.0 blank and 100.0 blank |

Style Designator:

Rectangular terminal/terminals on one surface

NSN 5915-00-126-5956

Band Pass Filter - Page 2 of 2



Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A047b0