

View Online at <https://aerobasegroup.com/nsn/5915-00-128-8020>

Overall Length:

3.625 inches

Overall Height:

2.500 inches

Overall Width:

4.750 inches

Body Length:

2.625 inches

Body Width:

4.500 inches

Unthreaded Mounting Hole Diameter:

0.152 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

3.375 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

3.000 inches

Operating Temperature Range:

+0.0 to 85.0 degrees celsius

Average Life Rating In Hours:

10000.0

Reference Frequency Per Function:

2.6 kilohertz blank

Input Impedance Per Function W/load:

600.0 ohms blank

Output Impedance Per Function W/source Across Input:

600.0 ohms blank

Principal Circuitry Type Per Function:

Crystal blank

Inclosure Type:

Hermetically sealed

Mounting Facility Type And Quantity:

4 unthreaded hole

Insertion Loss At Reference Frequency Per Function In Decibels:

3.0 blank

Functional Terminal Type And Quantity:

1 tab, solder lug output 2nd function

Maximum Dielectric Withstanding Ac Rms Voltage:

500.0 volts at sea level

Specified Frequencies Of Discrimination Per Function:

1.20 kilohertz blank and 2.20 kilohertz blank and 2.20 kilohertz blank and 4.00 kilohertz blank

Body Material:

Metal

Frequency Band Width Per Function:

1.20 kilohertz blank and 4.00 kilohertz blank

Discrimination At Specificationified Frequencies Per Function In Decibels:

3.0 blank and 1.0 blank and 1.0 blank and 3.0 blank

Style Designator:

Rectangular terminal/terminals on opposite surfaces

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A047b0