

View Online at <https://aerobasegroup.com/nsn/5915-00-130-1796>

**Overall Length:**

Between 17.375 inches and 17.500 inches

**Body Length:**

Between 17.375 inches and 17.500 inches

**Body Width:**

Between 4.875 inches and 5.000 inches

**Body Height:**

Between 3.875 inches and 4.000 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:**

16.500 inches

**Vibration Resistance Range In Hertz:**

+10.0 to 55.0

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:**

4.000 inches

**Operating Temperature Range:**

+0.0 to 71.0 degrees celsius

**Input Impedance Per Function W/load:**

50.0 ohms 2nd radio interference 2nd function

**Power Line Frequency Rating Per Function In Hertz:**

66.0 2nd radio interference 2nd function

**Operating Current Rating Per Function In Amps:**

7.0 2nd radio interference 2nd function

**Maximum Voltage Drop Per Function:**

0.5 volts ac 2nd radio interference 2nd function

**Principal Circuitry Type Per Function:**

Inductance-capacitance 1st radio interference 1st function

**Output Terminal Manufacturer Code:**

71468

**Output Terminal Identification:**

Gs02-16s-5p

**Maximum Temperature Rise:**

25.0 degrees celsius

**Mounting Facility Screw Thread Series Designator:**

Unf

**Inclosure Type:**

Hermetically sealed

**Mounting Facility Type And Quantity:**

6 threaded hole

**Functional Terminal Type And Quantity:**

4 tab, solder lug input 1st function

**Operating Voltage Rating And Type Per Function:**

120.0 volts ac 1st radio interference 1st function

**Thread Size:**

0.190 inches

**Body Material:**

Metal

**Body Surface Treatment:**

Tin

**Style Designator:**

Rectangular terminal/terminals on opposite surfaces

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A047b0