

View Online at <https://aerobasegroup.com/nsn/5915-00-131-1057>

**Overall Length:**

2.500 inches

**Body Length:**

1.750 inches

**Body Width:**

1.250 inches

**Body Height:**

0.875 inches

**Unthreaded Mounting Hole Diameter:**

0.196 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:**

2.125 inches

**Vibration Resistance Range In Hertz:**

+5.0 to 2000.0

**Operating Temperature Range:**

-54.0/+95.0 degrees celsius

**Average Life Rating In Hours:**

10000.0

**Source Impedance Rating Per Function:**

50.0 ohms 2nd radio interference 2nd function

**Load Impedance Per Function:**

50.0 ohms 3rd radio interference 3rd function

**Power Line Frequency Rating Per Function In Hertz:**

400.0 3rd radio interference 3rd function

**Operating Current Rating Per Function In Amps:**

0.5 2nd radio interference 2nd function

**Maximum Voltage Drop Per Function:**

750.0 millivolts dc 3rd radio interference 3rd function

**Principal Circuitry Type Per Function:**

Inductance-capacitance 3rd radio interference 3rd function

**Maximum Temperature Rise:**

25.0 degrees celsius

**Inclosure Type:**

Encased

**Mounting Facility Type And Quantity:**

2 unthreaded hole

**Functional Terminal Type And Quantity:**

2 tab, solder lug output 2nd function

**Operating Voltage Rating And Type Per Function:**

130.0 volts ac 3rd radio interference 3rd function and 400.0 volts dc 3rd radio interference 3rd function

**Body Material:**

Metal

**Maximum Dielectric Withstanding Dc Voltage:**

600.0 volts at sea level

**Unpackaged Unit Weight:**

4.500 ounces

**Style Designator:**

Rectangular terminal/terminals on opposite surfaces

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiiq:**

A047b0