

View Online at <https://aerobasegroup.com/nsn/5915-00-132-3493>

Overall Height:

1.350 inches

Body Length:

1.350 inches

Body Width:

1.350 inches

Body Height:

1.000 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

1.000 inches

Vibration Resistance Range In Hertz:

+10.0 to 55.0

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

1.000 inches

Operating Temperature Range:

+0.0 to 55.0 degrees celsius

Average Life Rating In Hours:

10000.0

Reference Frequency Per Function:

12.0 kilohertz blank

Input Impedance Per Function W/load:

120.0 ohms blank

Output Impedance Per Function W/source Across Input:

240.0 ohms blank

Principal Circuitry Type Per Function:

Crystal blank

Mounting Facility Screw Thread Series Designator:

Unc

Inclosure Type:

Encased

Mounting Facility Type And Quantity:

1 threaded stud 1st function

Insertion Loss At Reference Frequency Per Function In Decibels:

5.0 blank

Functional Terminal Type And Quantity:

2 solder stud output 2nd function

Maximum Dielectric Withstanding Ac Rms Voltage:

500.0 volts at sea level

Specified Frequencies Of Discrimination Per Function:

10.00 kilohertz blank and 12.00 kilohertz blank and 12.00 kilohertz blank and 14.00 kilohertz blank

Thread Size:

0.138 inches

Frequency Band Width Per Function:

10.00 kilohertz blank and 14.00 kilohertz blank

Discrimination At Specificationified Frequencies Per Function In Decibels:

3.0 blank and 0.0 blank and 0.0 blank and 3.0 blank

Style Designator:

Rectangular terminal/terminals on one surface

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A047b0