

View Online at <https://aerobasegroup.com/nsn/5915-00-132-4379>

Overall Length:

3.250 inches

Body Length:

2.812 inches

Body Width:

1.031 inches

Body Height:

1.000 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

2.375 inches

Vibration Resistance Range In Hertz:

+5.0 to 500.0

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

0.625 inches

Operating Temperature Range:

-10.0 to 75.0 degrees celsius

Reference Frequency Per Function:

307.5 kilohertz blank

Input Impedance Per Function W/load:

1.0 kilohms blank

Output Impedance Per Function W/source Across Input:

1.0 kilohms blank

Principal Circuitry Type Per Function:

Crystal blank

Mounting Facility Screw Thread Series Designator:

Unc

Inclosure Type:

Encased

Mounting Facility Type And Quantity:

4 threaded hole

Insertion Loss At Reference Frequency Per Function In Decibels:

4.0 blank

Functional Terminal Type And Quantity:

2 wire loop output 2nd function

Maximum Dielectric Withstanding Ac Rms Voltage:

100.0 volts at sea level

Specified Frequencies Of Discrimination Per Function:

300.00 kilohertz blank and 307.475 kilohertz blank and 307.525 kilohertz blank and 315.00 kilohertz blank

Thread Size:

0.112 inches

Body Material:

Metal

Frequency Band Width Per Function:

307.475 kilohertz blank and 307.525 kilohertz blank

Discrimination At Specificationified Frequencies Per Function In Decibels:

60.0 blank and 4.0 blank and 4.0 blank and 60.0 blank

Style Designator:

Rectangular terminal/terminals on opposite surfaces

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A047b0