

View Online at <https://aerobasegroup.com/nsn/5915-00-133-0448>

Overall Height:

0.625 inches

Body Length:

0.750 inches

Body Width:

0.750 inches

Body Height:

0.250 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

0.562 inches

Vibration Resistance Range In Hertz:

+10.0 to 2000.0

Reference Frequency Per Function:

4.5 kilohertz blank

Input Impedance Per Function W/load:

10.0 kilohms blank

Output Impedance Per Function W/source Across Input:

10.0 kilohms blank

Mounting Facility Screw Thread Series Designator:

Unc

Inclosure Type:

Hermetically sealed

Mounting Facility Type And Quantity:

2 threaded stud

Insertion Loss At Reference Frequency Per Function In Decibels:

6.0 blank

Functional Terminal Type And Quantity:

1 tab, solder lug output 2nd function

Maximum Dielectric Withstanding Ac Rms Voltage:

500.0 kilovolts at sea level

Specified Frequencies Of Discrimination Per Function:

1.00 kilohertz blank and 8.00 kilohertz blank and 12.00 kilohertz blank and 16.00 kilohertz blank

Thread Size:

0.112 inches

Body Material:

Metal

Frequency Band Width Per Function:

1.00 kilohertz blank and 8.00 kilohertz blank

Discrimination At Specificationified Frequencies Per Function In Decibels:

6.0 blank and 6.0 blank and 30.0 blank and 40.0 blank

Style Designator:

Rectangular terminal/terminals on one surface

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A047b0