

View Online at <https://aerobasegroup.com/nsn/5915-00-133-0448>

**Overall Height:**

0.625 inches

**Body Length:**

0.750 inches

**Body Width:**

0.750 inches

**Body Height:**

0.250 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:**

0.562 inches

**Vibration Resistance Range In Hertz:**

+10.0 to 2000.0

**Reference Frequency Per Function:**

4.5 kilohertz blank

**Input Impedance Per Function W/load:**

10.0 kilohms blank

**Output Impedance Per Function W/source Across Input:**

10.0 kilohms blank

**Mounting Facility Screw Thread Series Designator:**

Unc

**Inclosure Type:**

Hermetically sealed

**Mounting Facility Type And Quantity:**

2 threaded stud

**Insertion Loss At Reference Frequency Per Function In Decibels:**

6.0 blank

**Functional Terminal Type And Quantity:**

1 tab, solder lug output 2nd function

**Maximum Dielectric Withstanding Ac Rms Voltage:**

500.0 kilovolts at sea level

**Specified Frequencies Of Discrimination Per Function:**

1.00 kilohertz blank and 8.00 kilohertz blank and 12.00 kilohertz blank and 16.00 kilohertz blank

**Thread Size:**

0.112 inches

**Body Material:**

Metal

**Frequency Band Width Per Function:**

1.00 kilohertz blank and 8.00 kilohertz blank

**Discrimination At Specificationified Frequencies Per Function In Decibels:**

6.0 blank and 6.0 blank and 30.0 blank and 40.0 blank

**Style Designator:**

Rectangular terminal/terminals on one surface

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A047b0