

View Online at <https://aerobasegroup.com/nsn/5915-00-135-5995>

Overall Length:

3.124 inches

Body Length:

2.500 inches

Body Width:

1.750 inches

Body Height:

0.875 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

2.000 inches

Vibration Resistance Range In Hertz:

+5.0 to 500.0

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

1.250 inches

Operating Temperature Range:

-15.0 to 75.0 degrees celsius

Reference Frequency Per Function:

300.0 kilohertz blank

Source Impedance Rating Per Function:

1.0 kilohms blank

Load Impedance Per Function:

1.0 kilohms blank

Input Impedance Per Function W/load:

1.0 kilohms blank

Output Impedance Per Function W/source Across Input:

1.0 kilohms blank

Principal Circuitry Type Per Function:

Crystal blank

Mounting Facility Screw Thread Series Designator:

Unc

Inclosure Type:

Hermetically sealed

Mounting Facility Type And Quantity:

4 threaded hole

Insertion Loss At Reference Frequency Per Function In Decibels:

4.0 blank

Functional Terminal Type And Quantity:

2 wire hook output 2nd function

Specified Frequencies Of Discrimination Per Function:

298.30 kilohertz blank and 299.90 kilohertz blank and 300.10 kilohertz blank and 301.70 kilohertz blank

Thread Size:

0.112 inches

Frequency Band Width Per Function:

299.90 kilohertz blank and 300.10 kilohertz blank

Discrimination At Specificationified Frequencies Per Function In Decibels:

35.0 blank and 3.0 blank and 3.0 blank and 35.0 blank

Style Designator:

Rectangular terminal/terminals on opposite surfaces

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A047b0