

View Online at <https://aerobasegroup.com/nsn/5915-00-135-5995>

**Overall Length:**

3.124 inches

**Body Length:**

2.500 inches

**Body Width:**

1.750 inches

**Body Height:**

0.875 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:**

2.000 inches

**Vibration Resistance Range In Hertz:**

+5.0 to 500.0

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:**

1.250 inches

**Operating Temperature Range:**

-15.0 to 75.0 degrees celsius

**Reference Frequency Per Function:**

300.0 kilohertz blank

**Source Impedance Rating Per Function:**

1.0 kilohms blank

**Load Impedance Per Function:**

1.0 kilohms blank

**Input Impedance Per Function W/load:**

1.0 kilohms blank

**Output Impedance Per Function W/source Across Input:**

1.0 kilohms blank

**Principal Circuitry Type Per Function:**

Crystal blank

**Mounting Facility Screw Thread Series Designator:**

Unc

**Inclosure Type:**

Hermetically sealed

**Mounting Facility Type And Quantity:**

4 threaded hole

**Insertion Loss At Reference Frequency Per Function In Decibels:**

4.0 blank

**Functional Terminal Type And Quantity:**

2 wire hook output 2nd function

**Specified Frequencies Of Discrimination Per Function:**

298.30 kilohertz blank and 299.90 kilohertz blank and 300.10 kilohertz blank and 301.70 kilohertz blank

**Thread Size:**

0.112 inches

**Frequency Band Width Per Function:**

299.90 kilohertz blank and 300.10 kilohertz blank

**Discrimination At Specificationified Frequencies Per Function In Decibels:**

35.0 blank and 3.0 blank and 3.0 blank and 35.0 blank

**Style Designator:**

Rectangular terminal/terminals on opposite surfaces

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A047b0