

View Online at https://aerobasegroup.com/nsn/5915-00-137-3002

Overall Length: 3.499 inches Body Length: 0.454 inches Body Outside Diameter: 1.062 inches Operating Tempurature Range: -54.0/+95.0 degrees celsius End Application: Ea-6b prowler aircraft Power Line Frequency Rating Per Function In Hertz: 1200.0 blank Operating Current Rating Per Function In Amps: 3.5 blank Maximum Voltage Drop Per Function: 500.0 millivolts ac blank and 500.0 millivolts dc blank Principal Circuitry Type Per Function: Inductance-capacitance blank Mounting Facility Screw Thread Series Designator: Unf Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity: 1 threaded bushing Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 120.0 volts ac blank and 400.0 volts dc blank Thread Size: 0.375 inches Cirticality Code Justification: Feat Special Features:
Body Length:0.454 inchesBody Outside Diameter:1.062 inchesOperating Tempurature Range:-54.0/+95.0 degrees celsiusEnd Application:Ea-6b prowler aircraftPower Line Frequency Rating Per Function In Hertz:1200.0 blankOperating Current Rating Per Function In Amps:3.5 blankMaximum Voltage Drop Per Function:500.0 millivolts ac blank and 500.0 millivolts dc blankPrincipal Circuitry Type Per Function:Inductance-capacitance blankMounting Facility Screw Thread Series Designator:UnfInclosure Type:Hermetically sealedMounting Facility Type And Quantity:1 threaded bushingFunctional Terminal Type And Quantity:1 tab, solder lug output 2nd functionOperating Voltage Rating And Type Per Function:120.0 volts ac blank and 400.0 volts dc blankThread Size:0.375 inchesCirticality Code Justification:FeatSpecial Features:
0.454 inches Body Outside Diameter: 1.062 inches Operating Tempurature Range: -54.0/+95.0 degrees celsius End Application: Ea-6b prowler aircraft Power Line Frequency Rating Per Function In Hertz: 1200.0 blank Operating Current Rating Per Function In Amps: 3.5 blank Maximum Voltage Drop Per Function: 500.0 millivolts ac blank and 500.0 millivolts dc blank Principal Circuitry Type Per Function: Inductance-capacitance blank Mounting Facility Screw Thread Series Designator: Unf Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity: 1 threaded bushing Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 120.0 volts ac blank and 400.0 volts dc blank Thread Size: 0.375 inches Criticality Code Justification: Feat Special Features:
Body Outside Diameter: 1.062 inches Operating Tempurature Range: -54.0/+95.0 degrees celsius End Application: Ea-6b prowler aircraft Power Line Frequency Rating Per Function In Hertz: 1200.0 blank Operating Current Rating Per Function In Amps: 3.5 blank Maximum Voltage Drop Per Function: 500.0 millivolts ac blank and 500.0 millivolts dc blank Principal Circuitry Type Per Function: Inductance-capacitance blank Mounting Facility Screw Thread Series Designator: Unf Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity: 1 threaded bushing Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 120.0 volts ac blank and 400.0 volts dc blank Thread Size: 0.375 inches Criticality Code Justification: Feat Special Features:
1.062 inchesOperating Tempurature Range:-54.0/+95.0 degrees celsiusEnd Application:Ea-6b prowler aircraftPower Line Frequency Rating Per Function In Hertz:1200.0 blankOperating Current Rating Per Function In Amps:3.5 blankMaximum Voltage Drop Per Function:500.0 millivolts ac blank and 500.0 millivolts dc blankPrincipal Circuitry Type Per Function:Inductance-capacitance blankMounting Facility Screw Thread Series Designator:UnfInclosure Type:Hermetically sealedMounting Facility Type And Quantity:1 threaded bushingFunctional Terminal Type And Quantity:1 tab, solder lug output 2nd functionOperating Voltage Rating And Type Per Function:1200. volts ac blank and 400.0 volts dc blankThread Size:0.375 inchesCirticality Code Justification:FeatSpecial Features:
Operating Tempurature Range:-54.0/+95.0 degrees celsiusEnd Application:Ea-6b prowler aircraftPower Line Frequency Rating Per Function In Hertz:1200.0 blankOperating Current Rating Per Function In Amps:3.5 blankMaximum Voltage Drop Per Function:500.0 millivolts ac blank and 500.0 millivolts dc blankPrincipal Circuitry Type Per Function:Inductance-capacitance blankMounting Facility Screw Thread Series Designator:UnfInclosure Type:Hermetically sealedMounting Facility Type And Quantity:1 threaded bushingFunctional Terminal Type And Quantity:1 tab, solder lug output 2nd functionOperating Voltage Rating And Type Per Function:1200. volts ac blank and 400.0 volts dc blankThread Size:0.375 inchesCriticality Code Justification:FeatSpecial Features:
 -54.0/+95.0 degrees celsius End Application: Ea-6b prowler aircraft Power Line Frequency Rating Per Function In Hertz: 1200.0 blank Operating Current Rating Per Function In Amps: 3.5 blank Maximum Voltage Drop Per Function: 500.0 millivolts ac blank and 500.0 millivolts dc blank Principal Circuitry Type Per Function: 1000 tractace-capacitance blank Mounting Facility Screw Thread Series Designator: Unf Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity: 1 threaded bushing Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 120.0 volts ac blank and 400.0 volts dc blank Thread Size: 0.375 inches Criticality Code Justification: Feat Special Features:
End Application: Ea-6b prowler aircraft Power Line Frequency Rating Per Function In Hertz: 1200.0 blank Operating Current Rating Per Function In Amps: 3.5 blank Maximum Voltage Drop Per Function: 500.0 millivolts ac blank and 500.0 millivolts dc blank Principal Circuitry Type Per Function: 100 millivolts ac blank and 500.0 millivolts dc blank Principal Circuitry Type Per Function: 100 millivolts ac blank and 500.0 millivolts dc blank Principal Circuitry Type Per Function: 100 millivolts ac blank and 500.0 millivolts dc blank Principal Circuitry Type Per Function: 100 millivolts ac blank and 500.0 millivolts dc blank Mounting Facility Screw Thread Series Designator: Unf Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity: 1 threaded bushing Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 120.0 volts ac blank and 400.0 volts dc blank Thread Size: 0.375 inches Criticality Code Justification: Feat Special Features:
Ea-6b prowler aircraft Power Line Frequency Rating Per Function In Hertz: 1200.0 blank Operating Current Rating Per Function In Amps: 3.5 blank Maximum Voltage Drop Per Function: 500.0 millivolts ac blank and 500.0 millivolts dc blank Principal Circuitry Type Per Function: Inductance-capacitance blank Mounting Facility Screw Thread Series Designator: Unf Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity: 1 threaded bushing Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 120.0 volts ac blank and 400.0 volts dc blank Thread Size: 0.375 inches Cirticality Code Justification: Feat Special Features:
Power Line Frequency Rating Per Function In Hertz:1200.0 blankOperating Current Rating Per Function In Amps:3.5 blankMaximum Voltage Drop Per Function:500.0 millivolts ac blank and 500.0 millivolts dc blankPrincipal Circuitry Type Per Function:Inductance-capacitance blankMounting Facility Screw Thread Series Designator:UnfInclosure Type:Hermetically sealedMounting Facility Type And Quantity:1 threaded bushingFunctional Terminal Type And Quantity:1 tab, solder lug output 2nd functionOperating Voltage Rating And Type Per Function:120.0 volts ac blank and 400.0 volts dc blankThread Size:0.375 inchesCirticality Code Justification:FeatSpecial Features:
1200.0 blank Operating Current Rating Per Function In Amps: 3.5 blank Maximum Voltage Drop Per Function: 500.0 millivolts ac blank and 500.0 millivolts dc blank Principal Circuitry Type Per Function: Inductance-capacitance blank Mounting Facility Screw Thread Series Designator: Unf Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity: 1 threaded bushing Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 120.0 volts ac blank and 400.0 volts dc blank Thread Size: 0.375 inches Criticality Code Justification: Feat Special Features:
Operating Current Rating Per Function In Amps:3.5 blankMaximum Voltage Drop Per Function:500.0 millivolts ac blank and 500.0 millivolts dc blankPrincipal Circuitry Type Per Function:Inductance-capacitance blankMounting Facility Screw Thread Series Designator:UnfInclosure Type:Hermetically sealedMounting Facility Type And Quantity:1 threaded bushingFunctional Terminal Type And Quantity:1 tab, solder lug output 2nd functionOperating Voltage Rating And Type Per Function:120.0 volts ac blank and 400.0 volts dc blankThread Size:0.375 inchesCriticality Code Justification:FeatSpecial Features:
 3.5 blank Maximum Voltage Drop Per Function: 500.0 millivolts ac blank and 500.0 millivolts dc blank Principal Circuitry Type Per Function: Inductance-capacitance blank Mounting Facility Screw Thread Series Designator: Unf Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity: 1 threaded bushing Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 120.0 volts ac blank and 400.0 volts dc blank Thread Size: 0.375 inches Criticality Code Justification: Feat Special Features:
Maximum Voltage Drop Per Function:500.0 millivolts ac blank and 500.0 millivolts dc blankPrincipal Circuitry Type Per Function:Inductance-capacitance blankMounting Facility Screw Thread Series Designator:UnfInclosure Type:Hermetically sealedMounting Facility Type And Quantity:1 threaded bushingFunctional Terminal Type And Quantity:1 tab, solder lug output 2nd functionOperating Voltage Rating And Type Per Function:120.0 volts ac blank and 400.0 volts dc blankThread Size:0.375 inchesCriticality Code Justification:FeatSpecial Features:
500.0 millivolts ac blank and 500.0 millivolts dc blank Principal Circuitry Type Per Function: Inductance-capacitance blank Mounting Facility Screw Thread Series Designator: Unf Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity: 1 threaded bushing Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 120.0 volts ac blank and 400.0 volts dc blank Thread Size: 0.375 inches Feat Feat Special Features:
Principal Circuitry Type Per Function:Inductance-capacitance blankMounting Facility Screw Thread Series Designator:UnfInclosure Type:Hermetically sealedMounting Facility Type And Quantity:1 threaded bushingFunctional Terminal Type And Quantity:1 tab, solder lug output 2nd functionOperating Voltage Rating And Type Per Function:120.0 volts ac blank and 400.0 volts dc blankThread Size:0.375 inchesCriticality Code Justification:FeatSpecial Features:
Inductance-capacitance blank Mounting Facility Screw Thread Series Designator: Unf Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity: 1 threaded bushing Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 120.0 volts ac blank and 400.0 volts dc blank Thread Size: 0.375 inches Criticality Code Justification: Feat Special Features:
Mounting Facility Screw Thread Series Designator: Unf Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity: 1 threaded bushing Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 120.0 volts ac blank and 400.0 volts dc blank Thread Size: 0.375 inches Criticality Code Justification: Feat Special Features:
Unf Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity: 1 threaded bushing Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 120.0 volts ac blank and 400.0 volts dc blank Thread Size: 0.375 inches Criticality Code Justification: Feat Special Features:
Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity: 1 threaded bushing Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 120.0 volts ac blank and 400.0 volts dc blank Thread Size: 0.375 inches Criticality Code Justification: Feat Special Features:
Hermetically sealed Mounting Facility Type And Quantity: 1 threaded bushing Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 120.0 volts ac blank and 400.0 volts dc blank Thread Size: 0.375 inches Criticality Code Justification: Feat Special Features:
Mounting Facility Type And Quantity: 1 threaded bushing Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 120.0 volts ac blank and 400.0 volts dc blank Thread Size: 0.375 inches Criticality Code Justification: Feat Special Features:
1 threaded bushing Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 120.0 volts ac blank and 400.0 volts dc blank Thread Size: 0.375 inches Criticality Code Justification: Feat Special Features:
Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 120.0 volts ac blank and 400.0 volts dc blank Thread Size: 0.375 inches Criticality Code Justification: Feat Special Features:
1 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 120.0 volts ac blank and 400.0 volts dc blank Thread Size: 0.375 inches Criticality Code Justification: Feat Special Features:
Operating Voltage Rating And Type Per Function: 120.0 volts ac blank and 400.0 volts dc blank Thread Size: 0.375 inches Criticality Code Justification: Feat Special Features:
120.0 volts ac blank and 400.0 volts dc blank Thread Size: 0.375 inches Criticality Code Justification: Feat Special Features:
Thread Size: 0.375 inches Criticality Code Justification: Feat Special Features:
0.375 inches Criticality Code Justification: Feat Special Features:
Criticality Code Justification: Feat Special Features:
Feat Special Features:
Special Features:
Mannan evetere eccential
Weapon system essential
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli
Fiig: