

View Online at <https://aerobasegroup.com/nsn/5915-00-153-3590>

Reference Frequency Per Function:

500.0 kilohertz 2nd low pass 2nd function

Principal Circuitry Type Per Function:

Inductance-capacitance 2nd low pass 2nd function

Mounting Facility Screw Thread Series Designator:

Unc

Inclosure Type:

Encased

Mounting Facility Type And Quantity:

1 threaded stud

Insertion Loss At Reference Frequency Per Function In Decibels:

10.0 1st low pass 1st function

Functional Terminal Type And Quantity:

2 solder stud output 2nd function

Specified Frequencies Of Discrimination Per Function:

0.00 hertz 2nd low pass and 1.00 megahertz 2nd low pass and 2.00 megahertz 2nd low pass and 25.00 megahertz 2nd low pass

Thread Size:

0.112 inches

Frequency Band Width Per Function:

0.00 hertz 2nd low pass and 1.00 megahertz 2nd low pass

Discrimination At Specificationified Frequencies Per Function In Decibels:

0.0 2nd low pass and 10.0 2nd low pass and 60.0 2nd low pass and 50.0 2nd low pass

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A047b0