

View Online at <https://aerobasegroup.com/nsn/5915-00-153-3590>

**Reference Frequency Per Function:**

500.0 kilohertz 2nd low pass 2nd function

**Principal Circuitry Type Per Function:**

Inductance-capacitance 2nd low pass 2nd function

**Mounting Facility Screw Thread Series Designator:**

Unc

**Inclosure Type:**

Encased

**Mounting Facility Type And Quantity:**

1 threaded stud

**Insertion Loss At Reference Frequency Per Function In Decibels:**

10.0 1st low pass 1st function

**Functional Terminal Type And Quantity:**

2 solder stud output 2nd function

**Specified Frequencies Of Discrimination Per Function:**

0.00 hertz 2nd low pass and 1.00 megahertz 2nd low pass and 2.00 megahertz 2nd low pass and 25.00 megahertz 2nd low pass

**Thread Size:**

0.112 inches

**Frequency Band Width Per Function:**

0.00 hertz 2nd low pass and 1.00 megahertz 2nd low pass

**Discrimination At Specificationified Frequencies Per Function In Decibels:**

0.0 2nd low pass and 10.0 2nd low pass and 60.0 2nd low pass and 50.0 2nd low pass

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A047b0