

View Online at <https://aerobasegroup.com/nsn/5915-00-155-0596>

Overall Length:

1.138 inches

Body Length:

0.618 inches

Body Outside Diameter:

0.406 inches

Vibration Resistance Range In Hertz:

+10.0 to 2000.0

Operating Temperature Range:

-55.0 to 85.0 degrees celsius

Average Life Rating In Hours:

1000.0

Source Impedance Rating Per Function:

50.0 ohms blank

Load Impedance Per Function:

50.0 ohms blank

Operating Current Rating Per Function In Amps:

3.0 blank

Maximum Voltage Drop Per Function:

180.0 millivolts dc blank

Principal Circuitry Type Per Function:

Inductance-capacitance blank

Full Load Insertion Loss Frequencies In Megahertz:

0.03 and 0.15 and 0.3 and 1.0 and 10.0 and 1000.0

Full Load Minimum Insertion Loss At Specificationified Frequency In Decibels:

14.0 and 28.0 and 34.0 and 50.0 and 70.0 and 70.0

Mounting Facility Screw Thread Series Designator:

Unf

Inclosure Type:

Hermetically sealed

Mounting Facility Type And Quantity:

1 threaded bushing

Functional Terminal Type And Quantity:

1 tab, solder lug output 2nd function

Operating Voltage Rating And Type Per Function:

80.0 volts dc blank

Thread Size:

0.250 inches

Maximum Dielectric Withstanding Dc Voltage:

160.0 volts at sea level and 100.0 volts at altitude

Special Features:

Inductor at mounting end

Unpackaged Unit Weight:

6.000 grams

Style Designator:

Round terminal/terminals on opposite surfaces

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A047b0