

View Online at <https://aerobasegroup.com/nsn/5915-00-163-3912>

**Overall Length:**

1.355 inches

**Body Length:**

0.550 inches

**Body Outside Diameter:**

0.375 inches

**Vibration Resistance Range In Hertz:**

+10.0 to 2000.0

**Operating Temperature Range:**

-55.0/+85.0 degrees celsius

**Source Impedance Rating Per Function:**

50.0 ohms blank

**Load Impedance Per Function:**

50.0 ohms blank

**Power Line Frequency Rating Per Function In Hertz:**

420.0 blank

**Operating Current Rating Per Function In Amps:**

5.0 blank

**Principal Circuitry Type Per Function:**

Inductance-capacitance blank

**Full Load Insertion Loss Frequencies In Megahertz:**

0.3 and 1.0 and 10.0 and 100.0 and 1000.0 and 10000.0

**Full Load Minimum Insertion Loss At Specificationified Frequency In Decibels:**

10.0 and 40.0 and 80.0 and 80.0 and 80.0 and 80.0

**Mounting Facility Screw Thread Series Designator:**

Unf

**Inclosure Type:**

Hermetically sealed

**Mounting Facility Type And Quantity:**

1 threaded bushing

**Functional Terminal Type And Quantity:**

1 tab, solder lug output 2nd function

**Operating Voltage Rating And Type Per Function:**

115.0 volts ac blank and 185.0 volts dc blank

**Thread Size:**

0.250 inches

**Maximum Dielectric Withstanding Dc Voltage:**

370.0 volts at sea level

**Style Designator:**

Round terminal/terminals on opposite surfaces

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A047b0