## NSN 5915-00-163-3912

Radio Frequency Interference Filter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5915-00-163-3912

**Overall Length:** 

1.355 inches

**Body Length:** 

0.550 inches

**Body Outside Diameter:** 

0.375 inches

Vibration Resistance Range In Hertz:

+10.0 to 2000.0

**Operating Tempurature Range:** 

-55.0/+85.0 degrees celsius

**Source Impedance Rating Per Function:** 

50.0 ohms blank

**Load Impedance Per Function:** 

50.0 ohms blank

**Power Line Frequency Rating Per Function In Hertz:** 

420.0 blank

**Operating Current Rating Per Function In Amps:** 

5.0 blank

**Principal Circuitry Type Per Function:** 

Inductance-capacitance blank

Full Load Insertion Loss Frequencies In Megahertz:

0.3 and 1.0 and 10.0 and 100.0 and 1000.0 and 10000.0

Full Load Minimum Insertion Loss At Specificationified Frequency In Decibels:

10.0 and 40.0 and 80.0 and 80.0 and 80.0 and

**Mounting Facility Screw Thread Series Designator:** 

Unf

**Inclosure Type:** 

Hermetically sealed

**Mounting Facility Type And Quantity:** 

1 threaded bushing

**Functional Terminal Type And Quantity:** 

1 tab, solder lug output 2nd function

**Operating Voltage Rating And Type Per Function:** 

115.0 volts ac blank and 185.0 volts dc blank

**Thread Size:** 

0.250 inches

**Maximum Dielectric Withstanding Dc Voltage:** 

370.0 volts at sea level

**Style Designator:** 

Round terminal/terminals on opposite surfaces

Shelf Life:

N/a

## NSN 5915-00-163-3912

Radio Frequency Interference Filter - Page 2 of 2



ш	ın	10	<i>(</i> )+	Measure:	

--

Demilitarization:

No

Fiig:

A047b0