

View Online at <https://aerobasegroup.com/nsn/5915-00-163-3936>

**Overall Length:**

1.337 inches

**Body Length:**

0.670 inches

**Body Outside Diameter:**

0.400 inches

**Vibration Resistance Range In Hertz:**

+10.0/+55.0

**Operating Temperature Range:**

-55.0 to 85.0 degrees celsius

**Source Impedance Rating Per Function:**

50.0 ohms blank

**Load Impedance Per Function:**

50.0 ohms blank

**Power Line Frequency Rating Per Function In Hertz:**

420.0 blank

**Operating Current Rating Per Function In Amps:**

1.5 blank

**Principal Circuitry Type Per Function:**

Inductance-capacitance blank

**Full Load Insertion Loss Frequencies In Megahertz:**

0.01 and 0.1 and 1.0 and 10.0 and 100.0 and 1000.0

**Full Load Minimum Insertion Loss At Specificationified Frequency In Decibels:**

5.0 and 20.0 and 60.0 and 60.0 and 60.0 and 60.0

**Mounting Facility Screw Thread Series Designator:**

Unf

**Inclosure Type:**

Hermetically sealed

**Mounting Facility Type And Quantity:**

1 threaded bushing 3rd function

**Functional Terminal Type And Quantity:**

1 tab, solder lug output 2nd function

**Operating Voltage Rating And Type Per Function:**

125.0 volts ac blank and 250.0 volts dc blank

**Thread Size:**

0.250 inches

**Maximum Dielectric Withstanding Dc Voltage:**

300.0 volts at sea level

**Style Designator:**

Round terminal/terminals on opposite surfaces

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A047b0