## NSN 5915-00-166-0363

Low Pass Filter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5915-00-166-0363
Overall Length:
8.190 inches
Body Outside Diameter:
0.440 inches
Unthreaded Mounting Hole Diameter:
0.156 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:
5.750 inches
Operating Tempurature Range:
-28.0 to 65.0 degrees celsius
Reference Frequency Per Function:
150.0 megahertz blank
Source Impedance Rating Per Function:
50.0 ohms blank
Load Impedance Per Function:
50.0 ohms blank
Voltage Standing Wave Ratio Per Function:
1.5 blank
Inclosure Type:
Encased
Mounting Facility Type And Quantity:
4 unthreaded hole
Insertion Loss At Reference Frequency Per Function In Decibels:
3.1 blank
Functional Terminal Type And Quantity:
1 connector, receptacle output 2nd function
Specified Frequencies Of Discrimination Per Function:
138.00 megahertz blank and 162.00 megahertz blank and 300.00 megahertz blank and 600.00 megahertz blank
Body Material:
Metal
Frequency Band Width Per Function:
138.00 megahertz blank and 162.00 megahertz blank
Discrimination At Specificationified Frequencies Per Function In Decibels:
3.0 blank and 3.0 blank and 40.0 blank and 40.0 blank
Special Features:
Unthreaded holes in mounting brackets
Style Designator:
Round terminal/terminals on opposite surfaces
Shelf Life:
N/a

--

**Unit Of Measure:** 

## NSN 5915-00-166-0363

Low Pass Filter - Page 2 of 2



Demilitarization:

No

Fiig:

A047b0